

Product Specifications

UP Latex Foam Rubber - Medium Grade

Description: UP foam is a superior grade cushioning material especially formulated from a blend of natural and synthetic latex. This open-cell formulation is designed to resist set and compression loss from normal use and is sufficient strength to permit use in contour designs where tailoring and comfort are desired. It is easy to cut, saw, convolute and slit to desired shapes or thickness. UP is also available with a fabric backing for added strength and easy sewing.

<u>Characteristic</u> Density	Method ASTM D-3575	Target 8.5 lbs/ft	Tolerance + 2 lbs/ft
50%Compression Set	ASTM D-1055	15%, max	
(Max %) Based on original height Tensile Strength (PSI)	ASTM D-412	8 min	
Elongation (%)	ASTM D-412	<u>></u> 50%	
RMA/ILD	33	25-45	
Color	Natural (off white), gray, custom colors available		
Standard Sheet Size: 24" or 36" x 60" (± 5/8")			

24" or 36" x 72" (± 3/4") 24" or 36" x 96" (± 1")

Specifications are subject to revision.

2100 Commerce Drive, Fremont, Ohio 43420 (419) 332-5531

Prepared by: Division Manager-Industrial Foam Approved by: MR

Approvals

Uncontrolled Copy if Printed

Document #: 7-IF-072

Revision #: 2

Revision Date: 4/15/2013

Page 1 of 1